IN THE CLAIMS:

1. (Currently Amended) A pickup apparatus for a disk player for optically readingout information on a disk arranged in the disk player comprising:

a pickup for irradiating a light on said disk and for receiving the light reflected from said disk;

a light-emitting portion for transmitting the light to said pickup;

a plate-shaped half mirror for reflecting the light outputted from said light emitting portion and for transmitting the light to said pickup, that the light from said pickup permeate;

a detecting portion whereon the light permeating through said half mirror incidents; and

a frame whereto said pickup, said light emitting portion, and said detecting portion are fixed at predetermined positions, wherein a <u>first</u> side part of said half mirror is fixed to a <u>first</u> vertical wall of said frame at <u>three two</u> points <u>and second side part of said half-mirror is fixed to a second vertical wall of said frame at one point</u> by using an adhesive agent.

Coop v Coop v Coop of policy

U.S. Patent Apple tion Serial No. 09/964,170 Attorney Docket No. 04995.030001

2. (Currently Amended) A pickup apparatus for the disk player for optically readingout information on a disk arranged in the disk player comprising:

a pickup for irradiating a light on said disk and for receiving the light reflected from said disk;

a light-emitting portion for transmitting the light to said pickup;

a plate-shaped half mirror for reflecting the light outputted from said light emitting portion and for transmitting the light to said pickup, that the light from said pickup permeate;

a detecting portion whereon the light permeating through said half mirror incidents; and

a frame whereto said pickup, said light emitting portion, and said detecting portion are fixed at predetermined positions, wherein a <u>first</u> side part of said half mirror is fixed to a <u>first</u> vertical wall of said frame at <u>three two</u> points <u>and second side part of said half-mirror is fixed to a second vertical wall of said frame at one point by using an adhesive agent, wherein <u>the</u> two of said three points are located near said light emitting portion.</u>

3. (Previously Presented) The pickup apparatus for the disk player according to claim 1, wherein said half mirror is fixed to said frame at a fixing part to which said light-emitting portion is fixed and at a part that is opposed to said fixing part.

3

- 4. (Original) The pickup apparatus for the disk player according to claim 1, wherein said adhesive agent is a photocuring resin.
- 5. (New) A method for affixing a half mirror in a pickup apparatus for a disk player, comprising:

tentatively fixing a first side part of half mirror at one point and a second side. We part of the half mirror a one point by an adhesive agent;

finely tuning the position of the half mirror;

tentatively fixing the first side part of the half mirror at another point by the adhesive agent; and

fixing the half mirror by curing the adhesive agent.